

Battery Guide for Golf Cars

MODEL NAME	ELECTRIC (E) GASOLINE (G)	BCI GROUP	LENGTH	WIDTH	HEIGHT	DRY WEIGHT (pounds)	WET WEIGHT (pounds)	TERMINAL TYPE	PLATES/CELL	CAPACITY	WARRANTY	INFORMATION	
Chloride Inc. Tampa, FL	Long Drive 85	E	GC-2	11-1/4	7-3/16	10-3/8	-	66.0	HN	19	85	None	250
	Long Drive 106	"	GC-2-H	11-3/8	"	"	-	71.0	NB	19	106	"	251
Douglas Battery Manufacturing Co. Winston-Salem, NC	DB-EV23	E	GC-2	10-1/4	7-1/4	10-3/8	53.0	69.0	C*	23	125	1 Yr.	252
	DB-1	"	"	"	"	"	49.0	65.0	C*	21	115	"	253
	DB-2	"	"	"	"	"	45.0	62.0	C*	19	100	"	254
	DB-3	"	"	"	"	"	41.0	58.5	C*	17	86	"	255
	24S-50	G	24	"	6-3/4	8-7/8	22.0	36.0	P	9	50/75⊕	2 Yr.	256
Exide Co. Horscham, PA	Ev-88	E	GC-2	11-11/32	7-3/16	10-3/8	40.8	60.2	PWN	19	80	Optional	257
	EV-III	"	"	"	"	"	"	"	"	"	82	"	258
	EE-IV	"	"	"	"	"	47.6	65.5	"	"	97	"	259
	PV-23-3	"	"	"	"	"	49.4	65.0	"	22	125	"	260
General Battery Corp. Reading, PA	200Z	E	GC-2	10-7/8	7-1/8	10-5/16	-	62.0	P*	19	90	PR	261
	200C	"	"	"	"	"	-	"	WN	19	90	"	262
	250C	"	"	"	"	"	65	WNO**	"	107	"	"	263
	250Z	"	"	10-7/8	"	"	-	"	P*	"	"	"	264
	225C	"	"	10-15/16	"	"	-	64	WNO**	"	100	"	265
	225Z	"	"	10-7/8	"	"	-	"	P*	"	"	"	266
Gould, Inc. Mendota Heights, MN	220	E	GC-2	10-7/8	7-1/8	10-1/4	-	61.0	OP*	19	100	1/2 Yr.	267
	"	"	"	"	"	"	-	"	P	"	"	"	268
	195	"	"	"	"	"	-	58.0	OP*	17	88	"	269
	"	"	"	"	"	"	-	"	P	"	"	"	270
	24-GP-3	G	24	8-3/4	6-3/4	10-1/4	25.0	37.0	P	9	50/70⊕	"	271
Prestolite Battery Division Toledo, OH	9915X	E	GC-2	10.38	7.14	11.59	47.3	65.0	CS	17	110	2 Yr.	272
	9914X	"	"	"	"	"	"	"	"	15	90	1-1/2 Yr.	273
SGL Batteries Mfg. Co. Detroit, MI	2HGC	E	GC-2H	10-5/16	7-1/8	10-1/4	-	66	P, C GC, L	17	85	Optional	274
	2HGL-HC	"	GC-2H-HC	"	"	"	-	69	"	"	100	"	275
	2HGC-EC	"	GC-2H-EC	"	"	"	-	63	"	"	75	"	276
	22F	G	22-F	9-1/2	6-7/8	8-15/16	-	33	"	9	50/65⊕	"	277
Trojan Battery Co.	T-135	E	GC-2H	11-1/2	7-1/16	10-3/8	59.0	73.0	A, WN, U*	19	135	1 Yr.	278
	T-105	"	"	"	"	"	51.0	61.0	"	17	105	"	279
	T-90	"	GC-2	10-1/4	"	"	46.0	58.0	"	"	90	"	280
	CS-22	G	22F	8-3/8	6-13/16	9-1/2	24.0	32.0	"	9	55/80⊕	1 Yr.	281
	HS-24	"	24	8-3/4	6-3/4	10-1/4	26.0	38.0	"	"	53/90⊕	1 Yr.	282

*indicates cadmium-plated hole
**indicates cadmium-plated stud

⊕ When this symbol appears, the rating is amp hours/reserve capacity in minutes. Otherwise, the data indicates capacity in minutes at 75-amp discharge, 80° F., to 5.25 volts.

TERMINAL TYPE CODE: A=Angle, C=Combination, HN=Hex Nut, NB=Nut and Bolt, OP^{1/2}+Offset Post with stud and wing nut, P=Standard Automotive SAE Post, U=Universal, WN=Wing Nut



Chloride

Douglas

Exide

General

Prestolite