THE VERTIRAKES

P.V.R. (Pedestrian Vertirake)

- for Golf greens, Bowling greens, Cricket pitches and Tennis courts.

J.V.R. (Junior Vertirake)

- for Golf course greens, Bowling turf, Fine lawns etc.

T.V.R. (Tractor Vertirake)

-for Golf course fairways, Municipal Parks, Sports pitches.







These three machines have been designed to remove all the thatch, thus stimulating recovery and growth of strong healthy grasses. You will find that each machine will clear the difficult, dead, matted, fibrous grass that is so often so difficult to get rid of.

We have a machine for every purpose from the small golf green to the largest Municipal playing fields. One great labour saving device we have fitted on our P.V.R. model is the very large glass fibre collecting box which saves an enormous amount of time and energy that would otherwise be wasted in sweeping up afterwards.

Write for full information on VERTIRAKES to:



H. PATTISSON & CO. LTD., STANMORE HILL WORKS, STANMORE, MIDDLESEX,



FOUNDED 1912

Published monthly for the benefit of greenkeepers, greenkeeping and the game of golf on behalf of the British Golf Greenkeepers Association

President:

Carl Bretherton

Vice-Presidents:

Sir William Carr P. Marshall
Gordon Wright W. Payne
F. W. Hawtree W. Mountain
S. Norgate C. H. Dix
I. G. Nicholls F. G. Catchpole
F. V. Southgate J. F. R. Wilson
P. Hazell B. C. Jennings
D. B. Hargreaves D. Craig

Chairman:

V. W. Smith 7 Sunningdale Close Handsworth Wood Birmingham 20

Vice-Chairman:

Hon. Secretary & Treasurer:

W. Heeles
7 Tentergate Close
Knaresborough
Yorks

Executive Committee:

Carl Bretherton (President)
G. Herrington D. H. Major
V. Smith P. McCarron
W. Heeles J. Simpson
A. A. Cockfield H. M. Walsh
H. Fry (Jun.) E. James
Adrian Robertshaw

Hon. Auditors:

Messrs. Smallfield Rawlins & Co. Candlewick House 116/126 Cannon Street London E.C.4

Hon. Solicitors:

Henry Dowding, LL.B. 203-205 High Street Orpington The Association is affiliated to the

The Association is affiliated to the English and Welsh Golf Unions

The British Golf Greenkeeper

CONTENTS

	Page
DRAINAGE PROBLEMS	5–9
NEWS	12
THE GREENKEEPERS	13
TURF STORY	14–17
DIARY DATES	18
SECTION NEWS	19–23

Front Cover Picture

Ransomes new Mounted Hydraulic 3 tractor mounted three unit mower which made its debut at the Institute of Groundsmanship International Exhibition, Motspur Park. See further deails on Page 11.

EDITORIAL ADVERTISEMENT AND SUBSCRIPTION OFFICES: Chilberton House, Doods Road, Reigate, Surrey. Telephone: Reigate 43521. SUBSCRIPTION RATE: £2.76 for 12 issues post paid. Published during the first week of each month. All rights reserved. Reproduction of original articles and photographs in whole or in part is prohibited. This Magazine shall not, without the written consent of the publishers first given, be re-sold, lent, hired out, or otherwise disposed of. Contributions and photographs of interest are invited.

LATEST COPY DATE: 1st of month prior to insertion.

TO INSERT A CLASSIFIED ADVERTISEMENT, write to the Advertisement Manager at the above address. The rate is £3.00 per single column inch. Remittance must be sent with order. Please state number of insertions required and write advertisement in block letters. Advertisements will be inserted in the first available issue.

Printed by Oli ers Printing Works (Battle) Ltd.

BOMFORD BANDIT 2500 steals every economy on large open space mowing...



Europe's widest flail mower, the **Bandit 2500** has an 8' 3" cutting head for mowing and mulching up to $4\frac{1}{2}$ acres per hour.

Using a standard 3 point linkage and p.t.o. shaft the fully guarded cutting head will deal with grass up to waist height. The light weight flails are reversible and easily replaced to minimise maintenance costs.

Also available Bandit 6ft. model, cutting up to 3 acres per hour.

BOMFORD Flail Mowers

Bomford & Evershed Ltd., Evesham; Worcestershire WR11 5SW. Tel; Bidford-on-Avon (078-988) 3383. Telex; 311081.

Drainage problems

THE surface drainage of a golf course is greatly influenced both by design and by the character of the soil. This applies to all areas of the course from putting greens to rough. Design should not only take account of the natural features of the site to produce good golfing holes at an acceptable cost, but should bear in mind the varying drainage characteristics and subsequent maintenance of the area.

These latter aspects are particularly important when siting a new green or moving an existing one. Low lying areas are generally best avoided. If these parts are not naturally boggy and ill drained (or extremely difficult to drain artificially) they will nearly always be affected by surface water from surrounding higher land. Some of these problems may be overcome on the green itself by use of drainage carpets with emptying drains and an improved soil mix. Even then such good drainage can be severely taxed by heavy run-off in

By D. F. Boocock, Advisory Officer, The Sports Turf Research Institute.

storm conditions. The surrounds and approaches to such greens, usually with unimproved soil and little or no tile drainage, can deteriorate seriously.

Where a green must be of necessity sited in a different situation like this, some help can be gained by reshaping the fairway or surround to direct surface water run-off to the side of the green and, of course, away from the next tee.



electric, telephone, and signal cables, water, gas, and oil pipes, sportsfield, and parks drainage

it's easier & cheaper with a SCOOP TRENCHER

Scoop Trenchers dig trenches 4, 6, and 8 inches wide, and up to 39 inches deep automatically in any soil condition at speeds of up to 100 yards per hour.

A built in winch ensure positive traction even in bad conditions. Transportation and work in confined areas is easy because Scoop Trenchers are small.

The digging chains have a breaking strain of 21 tons so Scoop Trenchers are robust too.

Their initial cost can be saved in only 2,000 yards of work.



Send NOW for full details of machine, and hire rates to:-

A. F. TRENCHERS LTD

Gosbecks Road, Colchester, Telephone 4441

MEW! SHIPMAN TURFCARE


Eliminates the guesswork!



Single Blade Sand Injector operating on a Golf Green

Scientific analysis of your soil enables us to:-

Eliminate Waterlogging Improve soil structure



Establish precise fertilizer requirements and Provide YOU with the complete prescriptive Turfcare Service.



Chipman Limited, Horsham, Sussex, RH12 2NR. Telephone Horsham 60341/5 and at Royal Chambers, Station Parade, Harrogate, Yorkshire HG1 1EP. Telephone Harrogate 68658 Wincanton Close, Ascot Drive, Derby DE2 8ST. Telephone Derby 364271/4

At a point clear of areas that may come into play the redirected water could be picked up by a catchwater drain, i.e. a piped drain trench laid to a positive outlet and backfilled almost to the surface with aggregate and topped off with finer materials.

It may also prove necessary to trap surface water run-off in an area of rough using strategically placed catchwater drains and, where even greater quantities of water might be expected off extensive sloping rough, an open ditch on the top side of the semi-rough may be necessary. Similar considerations apply where greens or tees are cut out of a sloping hillside. Surface water run-off which must be expected in these circumstances has to be adequately catered for.

Lift and re-lay

Surface featuring of putting surfaces and surrounds, particularly where these are acute as on some of the older greens, can cause many problems. High parts shed water too quickly and cannot, of course, take the pin. Low lying areas even where the natural soil is employed are expected to take the brunt of twelve months play in all weathers and ground conditions. Not unnaturally these places become compacted or the soil structure is destroyed and the lowest hollow becomes a pond after heavy rain. On new sites these pitfalls should be avoided but on the older greens they can often be overcome only by lifting and re-laying.

Tees are usually built up to some extent and thus avoid many problems created by surface run-off. However, as tees get to be 600 sq. yd. or more, which is common nowadays, there is a greater need to consider putting a fall on the surface to actually aid water run-off. The introduction of pipe drainage and soil improvement are also more likely to be needed.

In addition to the points already made, with new fairways it makes good sense to avoid cut and fill grading wherever possible since nothing is more damaging to natural drainage. Fairways treated in this manner often take a long time to become fully established and have persistent drainage problems.

On most soils bunkers will need to be drained and the drains should be linked into a convenient green or fairway drain or, as a last resort, taken to a soakaway in the rough. On very heavy impermeable soils deep bunkers are inappropriate and in this situation should be kept as shallow as possible, so as to be practically seif-draining with the sand level running out virtually at grass level on the low edges.

Soil characteristics are a major factor influencing the drainage of water through the playing surface. The speed of water percolation through the soil to either drains or a naturally free draining sub-soil materially influences the quality of all the main playing surfaces on a golf course. On new golf greens the best answer seems to be to provide a drainage carpet with emptying drains and a specially prepared sand/soil mix designed, as far as practicable in the light of present knowledge, to give good percolation rates and at the same time to provide a satisfactory medium for producing a quality turf and first class playing surface.

Fibre build-up

On existing greens, particularly inland on heavier soils, poor drainage and its side effects can be particularly trouble-some. Often surface drainage problems are linked mainly to surface conditions—fibre has been allowed to build up to such an extent that it behaves like a sponge and in wetter periods never really dries out. In this situation hollow tine forking, sandy top dressings, plus plenty of scarification at the appropriate season, combined perhaps with liming where necessary, can bring about considerable improvement.

In many cases, however, the problems lie with the soil. Compaction and dam-

Would you buy a mower from a firm that has produced only half a million or so?

If you're looking for gimmicks of course you wouldn't. Because it smacks too much of traditional values – universal appeal, continuity of design, and so on – and a determination to keep it that way.

Fortunately for the world's sportsmen (and women), groundsmen throughout 73 countries think differently. They go for robust construction, proven design, ready availability of spares and a reputation for reliability that dates from 1921.

They choose -

JACOBSEN

Jacobsen mowers are available in the UK from a national network of distributors, all of whom carry good stocks of essential spares and offer an expert technical and after-sales service. Over 80% of spares are stocked by Rolfe, suppliers of an extensive range of turf care equipment and sole importers in the UK of Jacobsen mowers.

Send now for Rolfe's 20-page brochure, price list and details of your nearest distributor.



ROLFE

Rolfe's International Turf Equipment Ltd.,

Winchester Hill, Romsey, Hampshire.

Tel: Romsey 513185 Telex: 47347 age to soil structure, whether caused by mishandling during construction or by play or by poor management, will inevitably result in slower water percolation into and through the top soil. If water can only penetrate slowly through the soil to the drainage then inevitably there will be periods when rainfall exceeds the rate of percolation and a wet soft surface or flooding will result.

This sort of problem has always been extremely difficult to put right. Surface treatments such as hollow tine forking are valuable and by this means the poor structured or compact top soil can be replaced in part by working a very sandy compost into the fork holes. This, of course, takes time and needs a lot of compost—never less than 6 lb. per sq. yd. after hollow tining otherwise a very soft surface could result after repeated treatments. This treatment, in autumn, combined with plenty of slit tine aera-

tion the rest of the year can bring about big improvements.

However, if the problems lie deeper than, say, the top 5 in., i.e. on many greens there is 9 in. depth of heavy soil over a drainage carpet of stone, or a poorly permeable clay sub-soil, attacking from the surface is much less successful. In these cases very often complete reconstruction has to be faced, and this is still a valid, though costly, solution particularly for the most difficult cases.

In recent years attention has focussed somewhat on shallow sub-soil cultivation with a specially developed, sharp vibrating blade that penetrates 6 or 7 in. deep. This can give some surface improvement, although benefits are confined to the top few inches of soil. The work may be disruptive and on a stony soil may not be possible at all, and tends to be rather short lived, since eventually the cracks and slits formed close up or become silted up.



SAND INJECTION

BY OUR SPECIALISED MACHINES
CAN TRANSFORM

WET GREENS AND FAIRWAYS

DEEP AERATION OF GREENS BY SUB-AIR MACHINE AT ANY TIME OF YEAR NO SURFACE DAMAGE

Very moderate charges include all transport and an experienced operator

We are unaware of any other machine which penetrates to seven inches yet keeps the greens undamaged and in play

Cambridge Soil Services Limited Girton Road, Cambridge Tel. 76002

Specialists in Science Based Drainage

EASTCOTE NURSERIES

(Solihull) LIMITED for

TREE MOVING

We now have available a complete range of Tree Moving equipment to transplant Trees up to 35'.

Hampton Road, Barston, Solihull, West Midlands

Tel: Hampton in Arden 2034



BLUEGRASS (Poa Pratensis)

Formally known as Warren's A-34

A Smooth Stalked Meadowgrass!

- RECOVERS QUICKLY FROM INJURY
- Highly disease resistant.
- Thrives in open sunlight and varying soil conditions.
- Withstands short mowing, down to ½ inch.
- . Withstands shade (up to 65%).
- Produces a dense green sward of turf.

BenSun

BLUEGRASS SEED costs less

1 Pound Sows 2,000 Sq. Ft.

(Over 1,000 seeds per sq. ft.)

HURST GUNSON COOPER TABER LTD. Witham, Essex CM8 2DX PHONE: Witham 516600 (SPD Code 0376)