


THESE ARE YOUR
1943 MODEL



TUFHORSE GOLF BAGS and GLOVES

All of our facilities (and then some) formerly devoted to meeting the nation-wide demand for Tufhorse golf bags, gloves and head covers are now producing a steady stream of victory products.

In the meanwhile, remember that Tufhorse golf accessories were made to give the longest possible service. Take care of them and they'll see you through.

Thousands of our younger golfers are battling it out on foreign fronts.

Back 'em up with BONDS here at home.

DES MOINES GLOVE & MFG. CO.
DES MOINES, IOWA



USED GOLF BALLS

renewed
for maximum life
and playability

HIGHEST GRADE REBUILT
GOLF BALLS—75c, 50c, 35c

FOR PRO TRADE ONLY

Buy and Sell at Standard Prices.
All Golf Balls Guaranteed

SPEEDY FACTORY SERVICE

Send them in—NOW!

GEORGE BRAID
4242 N. MENARD AVE., CHICAGO

if bed plate is not level it will be necessary to shim it or shim the pump or motor until they are perfectly level.

7. It is imperative that the two halves of flexible coupling which connect pump and motor be in perfect alignment; check by placing straight edge across top of the two halves of the flexible coupling. Straightedge should be perfectly parallel with both surfaces; if not, pump or motor must be shimmed until this is assured. Clearance of $\frac{1}{8}$ in. to $\frac{1}{4}$ in. must be allowed between both faces of flexible coupling when the unit is running; this clearance can be checked with a thickness gauge and must be equal at all points.

Piping System

8. Before allowing water to enter pipe lines check all drain openings and make sure they are closed. Allow water to enter lines at reduced pressure. Open up all water valves at high points on the system and also at all "dead-ends"; flush these locations until all air is exhausted from piping system.

9. When piping system is thoroughly free of air, increase pressure to working pressure and examine all water valves for leaks. Repair any found, for numerous small leaks are cumulative on any golf course irrigation system and total leakage can be considerable.

Sprinklers

10. All slow-moving, long-range sprinklers should be dismantled each year. Remove old grease thoroughly, wash and clean all moving parts, replace any that are unduly worn, assemble and pack with a suitable grade of grease. Power lawn mower, tractor, or water-pump grease is not usually suitable, for it often congeals at low temperatures and eventually slows down or stops sprinkler. One suitable grade of grease is Texaco 904.

Check all sprinkler nozzle tips for indentures; if any are found, ream out inside of nozzle until they are removed, or replace with new nozzle of suitable size.

Has golf classes—Percy Jarvis, pro at Maplewood (N. J.) CC, is conducting his fifth annual adult golf class at the South Orange-Maplewood Adult School. This year the attendance has been cut by gas rationing to 20 who take the full course of 10 lessons. Class sessions are 1½ hours. Beside the course of golf instruction, water safety and lifesaving courses are the only athletic courses in the school's program of instruction.