


# Products

## IMPACT DRIVE SPRINKLER

*Eliminates splash on either side*



Royal Coach Sprinkler, Inc. announces assembly line production of an anti-back splash, impact drive sprinkler that eliminates water splash on either side of the

sprinklers. Available in full, part or full and part circle models, the impact drive 17000 series sprinklers can be installed above ground or below ground.

The all metal sprinkler has a 1/2" NPT standard pipe fitting. The pop-up model has a 3/4" NPT. The 17000 series operates on the 35-50 psi range with a coverage diameter of 84'.

Write 216 on free information card

## WIRE LOCATOR

*Locate "lost" solenoids quickly*




Progressive Electronics Inc., Mesa, Arizona introduces its revolutionary TVL Model 520 - station wire and valve

solenoid locator. Now, locate lost or hidden solenoids as fast as you can walk to them, and at the same time; trace the path of the station control wires. Easy to use - easy to operate, the TVL is a real problem solver.

Write 218 on free information card

## FLAIL MOWER

*Features close wall cut*



The 72 HD TURBOMOWER has been designed for long, trouble-free service cutting grass


and scrub in rough conditions. Its floating link suspension allows it to follow the contours of undulating ground, reducing wear on linkage points; a facility for offsetting up to 20" to the left allows cutting close to walls and other barriers.

The machine's 5 1/2" diameter steel rotor has a 3/8" thick wall; it is dynamically balanced and fitted with spring steel cutters attached by spring steel shackles. It can be adjusted for height from 3/4" to 4 3/4". The heavy-duty, doublesealed and self-aligning rotor bearings have a diameter of 2 1/2". Drive is through a heavy-duty bevel gearbox and a cross shaft with double universal coupling to four final drive v-belts with self-adjusting tensioning.

Write 207 on free information card

## EARTH DRILL

*Offers more positive operator control*



Groundhog announces a New Model D-5 Earth Drill featuring several improvements to provide more positive operator control. The chief difference is a new

manually controlled clutch which stops auger rotation the instant the clutch releases. This greatly reduces any possibility of run-away torque effects.

Two-inch through 12" interchangeable augers with changeable blades and fishtail pilots are available for use with the Groundhog Model D-5. As many as necessary of the four heavy duty handles may be removed for drilling close to buildings or transporting the drill in a car trunk.

Write 213 on free information card

## HYDROPHOBIC COATING

*Repels water, prevents icing*




Clifford W. Estes Co. announces the availability of Vellox 140, their new hydrophobic coating system which imparts extreme water repellency to any

substrate to which it is applied. Surfaces coated with Vellox 140 refuse water to such an extent that a visible air layer, recognized as a silvery sheen, can be seen between the water and treated surface. Water in contact with these surfaces forms tiny droplets with no meniscus and literally roll across the surface in an almost frictionless manner. It is highly durable and applicable to almost any substrate.

Write 204 on free information card

## PRESSURE REGULATOR

*Features setable output pressure*




A new pressure regulator designed to provide a setable output pressure from a valve regardless of higher input pressures was recently introduced

by Rain Bird. The new regulator is available with a Schrader Valve and is designated Model "PRS". Designed for use on Rain Bird Model "E", "EA", "EF", "EFA", "EF-CP", "EFA-CP", and "EP" Series valves, the pressure regulator may be ordered assembled to the valve or as an individual unit used to convert any of the Rain Bird valves listed to pressure regulation.

Write 202 on free information card

## HEDGE TRIMMER

*Ten pound unit features 17-inch blade*



A new gasoline hedge trimmer - the HC-140 - introduced by Echo, Inc.


Echo's new HC-140 hedge trimmer, is powered by the quality Echo air-cooled, 14cc single-cycle gasoline engine and features lightweight, ten-pound construction with a 17-inch single blade cutting action on a two-sided blade.

The HC-140 trimmer is designed with an anti-vibration mounting for left handle and a right hand grip with a hand guard for safety.

Write 210 on free information card

## SWING JOINT

*Swivel ell will not seize or corrode*



King Bros. Industries of Valencia, California is pleased to announce Swing-Ell™, a swivel fitting for swing joint assemblies available in 1/2", 3/4" and 1" sizes.

Swing-Ell provides permanent protective action for swing joint assemblies in sprinkler systems. It will not seize up or corrode and does not leak under static pressure testing.

The fitting is a 90 degree threaded street ell, which swivels freely where the male threaded end meets the body of the ell. The movement is sealed by a washer in the body.

Write 212 on free information card

## REAR-MOUNT ROTARY

*Bush Hog cutter features high speed*



Bush Hog's new TM-5 rear-mount rotary cutter features a blade tip speed of 16,440 feet per minute. Three hardened alloy uplift blades

overlap 1 1/2 inches to mow and mulch a five-foot swath. A flexible mast, leveling chains, adjustable skid shoes and caster wheels enable the rotary cutter to float over uneven ground.

Cutting height adjusts from one to six inches. The enclosed 10-gauge steel deck features standard safety shields and discharges clippings to the rear. Bush Hog's new TM-5 fits 15 to 35 HP tractors with a category I three-point hitch and 540 rpm PTO. Weight is 350 pounds. The cutter is shipped to dealers preassembled except for A-frame, drive line, skids and wheels.

Write 217 on free information card