

Hemco Corporation, Independence, Mo., announces a new "Supreme" line of fiberglass tanks from 60- to 500-gallon capacity. The tanks are constructed of fiberglass woven roving to offer maximum structural and impact strength. They feature the new armorcoated interior of isophthalic resin applied to eliminate glass fraying and possible chemical attack to the interior. Accessories available include manholes, P.V.C. coated glassed-in cast iron fittings, baffles, sumps, flat areas and saddles. For more details, circle (701) on reply card.



Servis Equipment Company, Dallas, has introduced a light rotary cutter called the "Chico." The five-foot-wide a designed for grass mowing for small acreages and e buildings. Features include all-welded unitized construct precision-engineered gear box, dishpan-type blade of smooth undercarriage, and full-length skid shoes. Chico about 600 pounds and is for wheel-type tractors with point hitch and drawbar rating between 20 hp and w For more details, circle (702) on reply card.



American Pulley Company, Philadelphia, offers a compact sprayer with tractor hitch and is equipped with a four-nozzle boom to distribute spray over a five-foot swath. Spraying time is reduced up to 80% compared with models that must be hand drawn, the company says. Delivers three gallons of spray per minute, has 15- and 30-gallon tank sizes, offers adjustable pressure from 20 to 300 psi. For more details, circle (705) on reply card.





Century Engineering Corporation, Cedar Rapids, Ia., introduces an a full-length mechanical agitator for chemical spray tanks. This as can be added at any time to 125- to 400-gallon tanks which have end surfaces for sealing. No pump capacity is required for mech agitation, so smaller, lower-priced pumps, hoses and fittings a used. Fully-enclosed electric motor can be front, side or rear ma Five double paddles turn at less than 200 rpm. For more details, (706) on reply card.

Industrial Scientific Instruments, Ltd., Montreal, Quebec, and Rouses Point, N.Y., has developed a buyer's calculator. The pocket-size device calculates: Total cost for any given quantity and cost each, or alternatively cost each for any given quantity and total price with or without discounts; selling price, to give any required percent markup on cost, or to give any required percent profit on selling price; percentage profit on cost or on selling price. It's easy to use, even by per-sons unaccustomed to a slide rule. The Calculator is $4\frac{1}{2}$ " in diameter and is made from high grade opal white acrylic material with fully engraved scales. The \$7.95 unit is supplied with a plastic case. For more details, circle (709) on reply card.



Davies Can Company, Cleveland Ohio, offers this new five-gallo polyethylene pail suitable for cor rosive materials. Ideal for agricu tural chemicals and acids. Der resistant, one-piece construction. Fo details, circle (710) on reply card.





ingineering Development Corporation, San Angelo, Tex., in entirely new concept in applying pesticides and herbitom spraying. The foam, that looks and sticks like a good lather, allows spray chemicals to be placed where needed drift. Foamicide Spray is credited with reducing the of chemical needed by eliminating costly waste and inabsorption. Foamicide can be applied using anything endgun to helicopter. For details, circle (703) on reply card.



Tryco Manufacturing Company, Inc., Decatur, Ill., has introduced a new line of pressurized doubleseal suspension and mixed-liquids pumps. In the Sealsaver line, a liquid under pressure in the seal chamber lubricates the seals and the liquid pressure inside the chamber is always higher than pressure of liquid being pumped, so no abrasive can reach the seal face to wear it down. For more details, circle (704) on reply card.



Funigants, Hazelwood, Mo., announces a new p, throw-away container for its gelled methyl soil fumigant formulations. The "PresTaner" is to be the first non-returnable container to receive U. S. Transportation Department approval for this product. A special "Eagle Claw" can puncturing permits the forcing of air or nitrogen pressure in to force the gelled fumigant out the bottom. For tails, circle (707) on reply card.

systems, Bell-III., has a new prottling valve for ly adjusting the te to booms and to olution agitators. ton be set at any from open to comshut. It's built for to 125 psi. Conmaterials include duminum, stainless d steel. The valve nd seat are made n to provide longsurfaces and posi-1-off. Long, tapered surfaces assure aclow rate control at ustments. Adjustindle designed with to hold position of For more details, 11) on reply card.





Practical Products Corporation, Tulsa, Okla., has added to its pump line Model K301-5420. It's a 20 gpm @ 600 psi, 4-cylinder, H.D. pump, ball-bearing, ni resist cylinders, stainless steel valves. Kohler 4 hp engine with 6-1 reduction and electric starter and generator. Weight -350 lbs., Length-43", Width-20", Height-25". Ideal for big-tree spraying and wide-area weed and brush control. For more details, circle (708) on reply card.

Orline Products, Los Angeles, Calif., has introduced the Orline Yard-Arm power tool that prunes small tree limbs, edges walks and flower beds, shapes unruly bushes, cuts tall weeds, clears brush, and performs a variety of other chores. The Orline Yard-Arm is a six-foot power pole with engine at one end and several attachments at the other. Weighs 11 lbs. and is powered by 1 h.p. O&R industrial engine. It comes with an 8-inch circular saw and an 8-inch edging blade. For details, circle (712) on the reply card.

