### **Eastman Industries** Portland, Maine 800/760-1680

The HM1952 HoverMower from Eastman Industries is powered by a Suzuki 3.8-hp two-stroke engine and has a cutting width of 19 inches. The mower features a durable aluminum cutting disc with three Zytel composite metal-edged blades, a space-age plastic alloy deck for strength and durability and a 15-inch impeller that produces optimum air volume for hoverability and performance. With a cushion of air beneath the deck, the Hover-Mower can mow in any direction and in hard-to-reach areas without scalping. The model comes with 18gauge steel handles and a vibrationreducing engine mount. Cutting height is adjustable from 1 to 3 inches

Circle No. 258

### Encore Manufacturing Co. **Beatrice**, NE 402/228-4255

Encore's Prowler Front Cut has a dual path hydrostatic drive for more overall drive power, control and stability on slopes and around tight turns. Available in single or dual-tail wheels, the mower has a zero turning radius in both 52- and 61-inch cutting widths. A 20-hp liquidcooled Kawasaki or 22-hp aircooled Kohler engine is available. Also included is a flip-up deck.

Circle No. 259

### **Exmark Manufacturing Co. Beatrice**, NE 402/223-6300

Exmark has incorporated a 22hp Kawasaki, liquid-cooled engine into its Lazer Z. Features include 52or 60-inch full-floating decks, zeroturn maneuverability and a radiator positioned up-

Exmark Lazer Z Liquid-Cooled

44

top to draw clean and

cool air. Instant-Adjust allows cutting height adjustments in 0.25-inch increments from a seated position. The mower also includes a wavy radiator screen to increase air flow and prevent complete blockage. Circle No. 260

### John Deere **Research Triangle Park, NC** 800/537-8233

John Deere has the HD45 and the HD75 walk-behind hydrostatic mowers. The HD45 has a 14-hp overhead valve engine while the HD75 has 17 hp. They both are available with an oscillating 48- or 54-inch deck. but the HD45 also has a 36inch deck available. The models have unitized hydrostatic transmissions with on-the-go tracking; speed and direction control; and parking brakes. A speed control lock lets you return every time to your preset speed and adjusts without tools. The HD75 also has a standard electric start. Circle No. 261

### **Ferris Industries** Munnsville, NY 800/933-6175

Ferris Industries presents the ProCut Z Mid-mount zero-turn rider. The mower features a footoperated deck lift and jumbo 23inch tires, 25-hp Kohler engine, twin four-gallon fuel tanks, variable displacement hydro-drive system with Hydro Gear pumps and Ross wheel motors. Also featured is a 54or 61-inch cutting width and a cutting height of 1.5 to 5 inches in 0.25-inch increments.

The mower has the Independent Drive Systems (IDS), which uses two separate reservoirs and hydraulic drives to prevent cross contamination of oil, as well as the IS independent suspension system which allows each wheel to move up and down independently, smoothing out the roughest turf. Circle No. 262

Gravely **Brillion**, WI

## 800-GRAVELY

chine features maintenance-free

Gravely XL Spindles and Gravely's Stay-sharp tungsten carbide coated blades. A five-inch-high deck, a redesigned cutting chamber and a 21-inch-wide discharge tunnel provides maximum air flow to expel clippings faster. The mower also includes a hydraulic deck height control and self-adjusting belts, a ninegallon fuel capacity and 360-degree swivel antiscalp

The Gravely 260Z

model is available with a 25-hp

hp Robin EH65V engine.

Circle No. 263

**Great Dane** 

Sellersburg, IN

inch cutting height.

**Rocky River, OH** 

440/333-9250

Lesco

Circle No. 264

812/246-8770

Kohler Command CV25S or a 22-

Great Dane's walk-behind Zero

platform nearly at the center of zero

turn radius. The mower features a

48-, 52- and 61-inch cutter decks,

guard-B&S and Kohler engines and

a hydrostatic drive system. Also in-

cluded is a six-gallon fuel tank with

extra wide mouth fill and a 2- to 6-

Lesco's 48- and 54-inch float

deck rotary mowers were designed

to promote maximum air flow for

even dispersion of clippings while

providing ease in height adjustment

by a four-pin system for raising and

These hydro drive mowers with

dual hydro pumps and drive mowers

lowering the cutting deck.

16-hp to 23 hp Kawasaki, Van-

Turn Surfer includes a stand-on

rollers. The



Lesco "Float Deck" rotary mower with hydro drive

allow true zero turning radius while allowing for positive reverse and eliminating belt slippage in wet

> conditions. The twin ground-speed control levers allow for on-the-go adjustment to ensure straight-line track-

ing and hillside control. Both models have five-gallon capacity fuel tanks.

Lesco offers the 48-inch cutting deck model powered by a 17hp electric start Kawasaki engine and the 54-inch cutting deck model with a 20-hp electric start Kohler engine. Circle No. 265

### MTD **Cleveland**, OH 330/225-2600

MTD introduces the 2260 Wide Track Mower in its new line of "MTD Pro" series. The mower features a 22-hp Kohler Command V-Twin OHV Engine and floating stamped decks with pivoting axles available in 48-, 54- or 60-inch sizes. Its dual hydrostatic control lets the operator perform true zero turns with pistol grip operation and allows for easy adjustment with no down time.

The mower also includes two ground-speed dash lever controls, 1.25-inch tubing handle bars and a five-gallon plastic fuel tank. The flatresistant, extra wide 9 x 3.5-inch front caster wheels provide reduced compacting and easier maneuvering and create the better curb appeal of a finished cut.

The mower also features a 1- to 4.5-inch easy adjustment cutting height in 0.25-inch increments, re-

The Gravely 260Z zero-turn ma-

# **MOWING** guide

quiring no tools to change the height. Circle No. 266

### Howard Price Turf Chesterfield, MO 314/532-7000

Howard Price Turf introduces a new vacuum attachment for its 360Z. The collection container has a capacity of 10 bushels and may be dumped from the operator's seat. The turbine operates off the cutting unit, eliminating the need for an auxiliary engine. The vacuum can be installed or removed with three pull pins.

Circle No. 267

### Scag Power Equipment Mayville, WI 920/387-0100

The heavy-duty hydro drive system on the SCAG STHM provides smooth, even power to both wheels, controlled by a single foot-pedal control. A 13-quart nylon reservoir and heavy duty cooling radiator ensure longer drive system component life by preventing contamination and lowering temperatures.

The STHM Hydro Rider is available with 52-, 61- or 72-inch cutter deck and 20- or 22-hp Kohler Command engine. Optional accessories include a 44-gallon capacity grass catcher with auxiliary engine, a mulching plate and electric deck lift.

Circle No. 268

### Steiner Dalton, OH 330/828-0200

The model ZTM 325 Steiner tractor is packaged with a Kohler Command engine with 25 hp at 3600 rpm. The 2-wheel drive tractor features zero turning, dual fuel tanks and foot-operated electric deck height adjustment. Included is a single park level, antiscalp rollers, twin hydrostatic controls with flip handles and a 61-inch deck cutting height of 1 to 5 inches.

Circle No. 269

Textron TurfCare & Specialty Products Racine, WI 414/637-6711 Jacobsen's Turfcat 500 Series features the power of a liquidcooled Kubota diesel engine with 22.5-, 28- and 33-hp engines. Mowers include a 12-gallon fuel tank and an accelerator with an adjustable pedal stop for setting a consistent transport/mowing speed.





Jacobsen Turfcat 500

Four heavy-gauge steel cutting decks are available and a new deck mounting delivers consistent cutting heights from one to four inches, in half-inch increments.

The 500 series has a new all-hydraulic traction drive and self-adjusting turn-assist brakes on the wheels to help ensure sure-footed stability. The hydraulic system oil capacity has been increased to eight gallons, which helps the system run cooler and last longer.

Circle No. 270

### Toro Bloomington, MN

612/888-8801 The Toro Groundsmaster 3000 has

a variety of choices. Available with either a 33-hp liquid-cooled Peu-

housing. The fewer parts and the direct transfer of power will make for years of durable performance. The Groundsmaster 3000 also has a variety of decks available: 84" Guardian Recycler®, 84" Rear Discharge, 72" Guardian Recycler®, 72" Rear Discharge and the new Contour 82. Additional attachments include: rotary

broom, snow-thrower, debris blower and enclosed cab. Circle No. 271

### Walker Manufacturing Co. Fort Collins, CO 970/221-5614

A new sprayer attachment for the front of the Walker mower is easily mounted to all 42-, 48- and 54-inch Walker decks and offers a 96-inch spray pattern. The SP6640 Boom Sprayer features a 20-foot hose and adjustable spray tip that allows the operator to adjust the spray pattern from a 35-foot stream to a mist pattern.

Walker also has a "No-Catch" Deflector for a quick conversion of



**Toro Groundsmaster 3000** 



Walker "No-Catch" Deflector

the Walker Grass handling System mower to a rear discharge mower. The conversion can be made in seconds by installing the deflector in the back of the GHS catcher box door. Circle No. 272

### -----

### Woods Equipment Co. Rockford, III 414-255-0100

Woods Equipment Co. has added the model 6225 Mow'n Machine to its line of zero turn radius mowers and offers a 25-hp Kohler engine with a 48-, 52-, 61- or 72inch deck.

Woods' 6000 Series of Mow'n Machines feature eight engine options ranging from 14 to 25 hp, including diesel. The mowers are designed with a low, out-front, three-spindle deck, allowing easy mowing under shrubs and low hanging branches.

The products include instant forward and reverse action, dual lever controls and special operator comfort features to increase productivity. The spring-loaded attachment pins allow for quick attachment of the decks, snow throwers, sweepers or dozer blades.

Grass collection systems are available in 7.5-, 15- and 25- cubic ft. models. Woods' collection systems are composed of a detachable blower and twin plastic containers or a steel gravity hopper with a levercontrolled gravity dump system. Circle No 273