

Xtra, xtra...

Little Wonder says that its Xtra edger combines the maneuverability of a stick edger and the power of a wheeled edger. It weighs 16 lbs., features a cross-blade system for overgrown grass, and runs on a 34cc two-cycle engine.

For more information contact Little Wonder at 877/596-6337 or www.littlewonder.com / circle no. 250

Mow 'n go

Woods Equipment Company's redesigned F-Series Mow'n Machines feature hydrostatic drive trains, tilt-access decks, Hydro-Gear pumps, Parker-Ross wheel motors and 11-gal. fuel capacity. A true-float deck adjusts to contours well.

Standard inflatable 23 x 10.50

12-in. drive and 15-in. tail-wheel tires were selected

with traction and ground clearance in mind.

For more information contact Woods at 866/869-6637 / circle no. 251

Bite through branches

Kawasaki's two hedge trimmer models, the 30-in., single-sided model KHS750A and the 24-in., double-sided model KHD600A, are both powered by a two-cycle 23cc Kawasaki engine and feature rubber mounts for low vibration and a one-piece forged clutch drum. Their heat-treated blades feature high speed reciprocating movement, closely fitted upper and lower cutting edges and a chamfered tip. The fuel tank on both holds 1.1 pints.

For more information contact Kawasaki at www.kawasaki.com / circle no. 252

Snip snip

STIHL's Precision Series line of hand tools includes three pole pruners, three loppers, one hedge shear, four pruning saws, four pruners and three axes. The pole pruners feature adjustable pole length, bark cutter and hook, and revolving arm. The loppers come in three sizes



Wide trackin'

The new Toro Dingo TX 425 wide track compact utility loader is powered by a 25-hp air-cooled Kohler Command Pro Series engine and offers more than 35 quick-change attachments. Other features include a four-pump, independent hydraulic suspension and dedicated auxiliary hydraulic circuit that provides 11.2 gpm of flow at 3,000 psi of hydraulic power. Its dedicated track drive features dual Kevlar reinforced rubber tracks that offers full ground engagement with only 3.4 psi of ground pressure.

For more information contact Toro at 800/344-8676 or www.toro.com / circle no. 255

with a 1- or 2-in. cutting capacity, and the pruning saws come in four sizes with blades ranging from 6 to 13 in. Axes come in 14- and 24-in. handle lengths.

For more information contact STIHL at 800/467-8445 or www.stihlusa.com / circle no. 253

Edge like a pro

Turfco claims its Edge-R-Rite edger's oscillating blade cuts turf without throwing debris, making it safer to use in high traffic areas and easier to clean up after. It's designed for flowerbeds, but additional blades can be added to suit it for sidewalks, curbs, driveways and to cut in drainage. Depth control can be adjusted up to four inches.

For more information contact Turfco at 800/679-8201 or www.turfco.com / circle no. 254



Making the cut

Kubota Tractor Corp.'s diesel-powered 2- and 4-WD F60 Series front-mount mowers range from 22hp to 30 hp. They have a single-pedal operated hydrostatic transmission and auto-assist 4WD with dual-acting overrunning clutch system. They are available with 60- or 72-in. side discharge mowers, or come with a 60- or 72-in. rear discharge mower. Easy access tilt-up deck provides 8 in. ground clearance.

For more information contact Kubota at 888/458-2682 www.cat.com / circle no. 256



Drift containment

Be environmentally correct with the Falcon electric drift containment spray system. It's battery operated, comes with a tank, and no hose is required. Built from aluminum and polyethylene, it uses 10-in. tires for great flotation and easy pushing.

For information contact John Deere Inquiry Dept., P.O. Box 12217, Research Triangle Park, NC 27709 or www.johndeere.com / circle no. 257